



**Part N. ADD 5000-100**

## Product Information

The Industrial Smart Isolator Base senses and isolates short circuit faults on XP95 and Discovery loops and spurs.

The base is loop-powered, polarity sensitive and accepts the XPERT card to set the address of the associated device.

In short-circuit conditions the integral yellow LED is illuminated. The detector associated with the base remains active under short-circuit conditions. Power and signals to the affected section are restored automatically when the fault is cleared.

## Protocol Compatibility

The Isolating Base is intended for use with equipment using the Syncoln XP95 and Discovery communication protocol.

## Operation

Under normal operating conditions a low impedance is present between the -IN and -OUT terminals of the base so that power and signals pass to the next base in line.

If a short-circuit or abnormally low impedance occurs the fall in voltage is sensed and the base isolates the negative supply in the direction of the fault. The isolated section is tested using a current pulse every five seconds. When the short-circuit is removed, the power will automatically be restored.

If it is a requirement that no device is lost in the event of a single short-circuit fault every detector should be fitted to an isolating base.

In applications where it is not necessary to use an isolating base for each detector, up to twenty detectors or equivalent surge current may be installed between isolating bases.

## EMC Directive 2014/30/EU

The Industrial Smart Isolator Base not only complies with the essential requirements of the EMC Directive 2014/30/EU, with strengthened Design and use of highest quality materials it will withstand higher temperature and environmental shocks than normal series which makes it more durable and reliable in Industrial facilities.

A copy of the Declaration of Conformity is available from Syncoln on request.

Conformity of the Isolating Base with the EMC Directive, does not confer compliance with the directive on any apparatus or systems connected to it.

## Construction Products Regulation 305/2011/EU

The Isolating Base complies with the essential requirements of the Construction Products Regulation 305/2011/EU.

A copy of the Declaration of Performance is available from Syncoln on request.

## TECHNICAL DATA

All data is supplied subject to change without notice. Specifications are typical at 24 V, 23°C and 50% RH unless otherwise stated. a

<b>Supply Voltage</b>	17V-28 V dc plus 9 V dc Protocol Pulses	
<b>Isolation indicator</b>	Yellow LED, lit continuously in isolation condition	
<b>Current consumption</b>	at 18 V dc	23µA
	at 18 V dc	43µA
	at 18 V dc and adjacent sector isolated	4Ma
<b>Maximum line current</b>	Non-isolating continuous 1.0A transition into isolation 3.0A	
<b>Operating temperature</b>	-40 °C to +80°C	
<b>Storage temperature</b>	-50 °C to +90°C	
<b>Humidity (no condensing or icing)</b>	0% to 99% relative humidity	
<b>Approved use</b>	Indoor use only	
<b>Dimensions</b>	100 mm diameter x 24 mm Height	
<b>Weight</b>	110g	
<b>Materials</b>	<b>Body</b> White polycarbonate moulding <b>Terminals</b> Nickel plated stainless	